

Washdown Service/MSHA MINE Spray Hose

Hose designed for dust control in water spray operations, and underground mining.

TUBE: NBR Synthetic Rubber (ARPM Class B)

COVER: NBR/PVC Synthetic Rubber (ARPM Class B)
Yellow color, MSHA approved, Pin-Pricked

REINFORCEMENT: 1 steel wire braid

TEMPERATURE: -40°F to +212°F (-40°C to +100°C)

APPLICATION: For general washdown service as well as dust control in mining operations.

FEATURES:

- Meets MSHA flame resistance requirements
- High visibility yellow cover
- Cover is weather and abrasion resistant
- Uses 12 Series Hose Couplings



Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @68°F		Vacuum @68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb.ft.	KG/m	in.	mm	
4183-0075-300	3/4	19.0	1.14	29.0	1.	1000	69.0	n/a	0.44	0.66	7.9	200	300
4183-0100-200	1	25.4	1.45	36.8	1.	1000	69.0	n/a	0.65	0.96	9.8	250	200

Working pressure (W.P.) is temperature dependent.

Accessories



Stainless Hose Reels



Spray Nozzles



Washdown Stations



Tank Washing Nozzles